

LAVATRICI SANITARIE A BARRIERA SANITARY BARRIER WASHER EXTRACTOR

WB25 - WB35 - WB70



RENZACCI

STERILIZATION & INNOVATION

STERILIZATION & INNOVATION

WB25 - WB35 - WB70

DOTATA DEI PIU' MODERNI E SOFISTICATI SISTEMI DI CONTROLLO GESTIONE E SICUREZZA PERMETTENDO L'ASSOLUTA CERTEZZA DEL RAGGIUNGIMENTO DI RISULTATI IMPECCABILI E CERTI E GARANTENDO COSI' IGIENE E LAVAGGIO DI ALTISSIMA QUALITA'

UNA IMPORTANTE REALIZZAZIONE ADATTA PER OSPEDALI, CLINICHE, CASE DI RIPOSO E PER TUTTE QUELLE ATTIVITA' IN CUI E' NECESSARIA LA SEPARAZIONE TRA I CAPI SPORCHI E PULITI.

MOLTE SONO LE INNOVAZIONI PRESENTI IN QUESTA MACCHINA CHE LA DIVERSIFICA RISPETTO A QUANTO PRESENTE SUL MERCATO

PROVIDED WITH THE MOST MODERN AND SOPHISTICATED MANAGEMENT AND SAFETY CONTROL SYSTEMS, THUS ALLOWING ABSOLUTE CERTAINTY TO REACH FLAWLESS AND SURE RESULTS AND THUS GUARANTEEING HYGIENE AND WASHING OF HIGHEST QUALITY.

AN IMPORTANT IMPLEMENTATION SUITABLE FOR HOSPITALS, CLINICS, ELDERLY HOMES AND FOR ALL THOSE ACTIVITIES, WHERE IT IS NECESSARY TO SEPARATE DIRTY AND CLEAN GOODS.

MANY ARE THE INNOVATIONS PRESENT IN THIS MACHINE WHICH MAKES IT DIFFERENT WITH RESPECT TO THE MACHINES ON THE MARKET.

			WB25	WB35	WB70
Capacità di carico Rapporto di sbattimento	Load capacity Linen to capacity ratio	kg	23 1/10	35 1/10	70 1/10
Cesto: Volume Diametro Profondità	Drum: Volume Diameter Depth	l mm mm	233 692 620	360 760 795	700 1061 787
Velocità cesto: Lavaggio Centrifuga veloce Fattore G	Drum speed: Wash High speed extract G-factor	r.p.m. r.p.m. r.p.m.	20-45 950 350	20-42 900 360	25-42 900 360
Commissioni: Entrata acqua fredda Entrata acqua calda Entrata vapore Scarico acqua	Connections: Cold water inlet Hot water inlet Steam inlet Water drain	Ø Ø Ø Ø	3/4" 3/4" 1/2" 1" 1/2	3/4" 3/4" 1/2" 2" 1/2	1" 1" 1/2" 2" 1/2
Pressioni: Acqua Vapore	Pressure: Max. Water pressure Max. Steam pressure	bar bar	5 5	5 5	5 5
Consumi: Acqua fredda / ciclo Acqua calda / ciclo Vapore / ciclo *	Consumptions: Cold water / cycle Hot water / cycle Steam / cycle *	l l kg	160 70 20	265 112 35	460 165 55
Potenza elettrica: Inverter Motore Resistenze riscaldamento **	Electric power: Inverter Motor Heating elements **	kW kW kW	2,2 3,5 12	4 4,5 18	7,5 11 36
Dimensioni: Larghezza Profondità Altezza	Overall dimensions: Width Depth Height	mm mm mm	1150 1070 1450	1400 1200 1550	1500 1500 1850
Peso netto	Net weight	kg	550	800	1450
Livello sonoro	Sound level	dB(A)	<70	<70	<70
* - STEAM HEATED MODELS			** - ELECTRIC HEATED MODELS		

Descrizioni, dati, misure, colori, non sono impegnativi e possono variare senza alcun preavviso - Descriptions, poids, mesures, figures et couleurs sont données sans engagement de notre part - Beschreibungen, Gewichte, Maße, Bilder und Farben sind unverbindlich - Descripción, datos, medidas y colores se facilitan sin compromiso u pueden ser variados sin previo aviso - Description, weights, measurements, pictures are not binding.



Via Morandi, 13 - 06012 CITTA' DI CASTELLO (PG) - ITALY

Telefono +39-075-862961 - Fax +39-075-8559020

E-MAIL: renzacci@renzacci.it - INTERNET: <http://www.renzacci.it>