

I.D.

EVO

PRO SERIES

DRYCLEANING MACHINE



550 - 650 - 800



EVO PRO SERIES

550 - 650 - 800

Drycleaning division

MODELLO	MODELE	U.M.	550	650	350	MODEL	U.M.	550	650	800
Capacità per carica	Capacité par cycle	kg	22	27	35	Load capacity	lb	55	65	80
Tamburo:	Tambour:					Drum:				
Diametro	Diamètre	mm	1000	1060	1060	Diameter	in	39.4	41.8	41.8
Profondità	Profondeur	mm	520	565	750	Depth	in	20.5	22.3	29.5
Volume	Volume	dm ³	408	500	670	Volume	cu.ft.	14.6	17.9	23.5
Velocità di lavaggio	Vitesse de lavage	g/l'	38	36	36	Wash speed	rpm	38	36	36
Velocità di centrifuga	Vitesse 1 d'essorage	g/l'	450	450	450	Extract speed 1	rpm	450	450	450
Misure di ingombro:	Dimensions:					Overall dimensions:				
Larghezza	Largeur	mm	2000	2070	2070	Width	in	78.8	81.5	81.5
Profondità	Profondeur	mm	1500	1630	1630	Depth	in	59.0	64.2	64.2
Altezza	Hauteur	mm	2150	2270	2270	Height	in	84.7	89.4	89.4
Peso	Poids	kg	2100	2360	2800	Weight	lb	4620	5170	6160
Serbatoi:	Réservoirs:					Tanks:	US			
1° serbatoio	1° Réservoir	lt	170	190	240	1st Tank	gals	44.5	50	63
2° serbatoio	2° Réservoir	lt	170	190	240	2nd Tank	gals	44.5	50	63
3° serbatoio	3° Réservoir	lt	200	200	300	3rd Tank	gals	53	53	79
Capacità filtri:	Capacité filtres:					Filter capacity				
Superficie filtrante	Filtre Nylon	m ²	4,3	5,6	8,5	Filter surface	sq.ft.	45	60	90
Filtro decolorante	Filtre decolorante	N°	1	2	2	Decolorating filter	No.	1	2	
Filtro ecologico	Filtre ecologique	lt	65	85	50	Ecological type	US gals	7.9	7.9	13.2
Distillatore	Distillateur	lt	250	300	330	Still	US gals	66	79	87
Dati di installazione:	Données d'installation:					Installation data:				
Ingresso acqua	Entrée eau	∅	½"	½"	½"	Water inlet	∅	½"	½"	½"
Pressione min. acqua	Pression eau	bar	1,5	1,5	1,5	Min. water pressure	psi	21.5	21.5	21.5
Ingresso vapore	Entrée vapeur	∅	½"	½"	½"	Steam supply	∅	½"	½"	½"
Pressione max. vapore	Pression vapeur	bar	4,5	4,5	4,5	Max. steam pressure	psi	64	64	64
Potenza impiegata	Puissance employée					Installed power				
Versione vapore	Version vapeur	kw	7,8	9,5	11,5	Steam model	kw	7.8	9.5	11.5
Versione elettrica	Version électrique	kw	24,6	32,7	35	Electric model	kw	24.6	32.7	35
Motori:	Moteurs:					Motors:				
Lavaggio	Lavage	kw	2,2	2,2	4	Wash speed	kw	2.2	2.2	4
Ventilatore	Ventilateur	kw	1,5	1,5	1,5	Fan	kw	1.5	1.5	1.5
Pompa	Pompe	kw	0,75	1,1	1,1	Pump	kw	0.75	1.1	1.1
Filtro	Filtre	kw	0,35	0,75	0,75	Filter	kw	0.35	0.75	0.75
Gruppo frigorifero	Groupe frigo	kw	3	4,3	4,3	Refrigerating unit	kw	3	4.3	4.3

Descrizioni, dati, misure, colori non sono impegnativi e possono variare senza alcun preavviso.
 Descriptions, weights, measurements, pictures and colours are not binding.
 Descriptions, poids, mesures, figures et couleurs sont donnés sans engagement de notre part.

ITALIAN DRYCLEANING S.R.L.

Via XXV Aprile, 20
52100 Arezzo (AR) - Italy

Tel. ++39 075 8521264

Fax. ++39 075 8520717

Mail: sales@italiandrycleaning.it

Web: www.italiandrycleaning.it